

DELTAWELD 350

Deltaweld® 350 Specifications (Subject to change without notice.)



Amp/Volt Ranges	Rated Output	Amps Input at Rated Output, 60 Hz, 3-Phase				Dimensions	Net Weight
		230 V	460 V	KVA	KW		
20-400 A, 10-38 V	300 A at 29 VDC, 100% duty cycle	26.5	14.6	11.6	10.0	H: 22.36 in. (568 mm) (including lift eye)	115 lb. (52.2 kg)
	350 A at 31.5 VDC, 60% duty cycle	33.4	18.1	14.5	12.5	W: 15.35 in. (390 mm)	
	425 A at 35.25 VDC, 30% duty cycle	45.1	23.1	18.5	16.9	D: 29.15 in. (740 mm)	



Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

Intelix™ Feeder Specifications (Subject to change without notice.)



Input Power	Welding Power Source	Input Welding Circuit Rating	Wire Feed Speed	Wire Diameter Capacity	Maximum Spool Size Capacity	Dimensions	Net Weight
50 VDC	Deltaweld 350	600 A at 113 VDC, 60% duty cycle	Standard 50-780 ipm (1.3-19.8 m/min.)	.023-5/64 in. (0.6-2.0 mm)	18 in. (457 mm) 60 lb. (27 kg)	H: 16.25 in. (413 mm) W: 12.38 in. (314 mm) D: 27.88 in. (708 mm)	44.8 lb. (20.3 kg)



Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

Cotiza directo a nuestro correo (clic en el link):

[mailto: contactenos@saltec-mexico.com.mx?subject=Cotización](mailto:contactenos@saltec-mexico.com.mx?subject=Cotización)